



ECO-VAPOR COTE COATING

55-10

COLORS:

55-10 White

SERVICE TEMPERATURE

-20° to 200° F
(-28.9° to 93° C)

WATER VAPOR TRANSMISSION (ASTM E-96)

.04 Perms at .020" film (.5mm)

COVERAGE

25 sq. ft./gal (1.6 Liter/M2)

The coverage rate is dependent on the surface being covered and the application method.

WEIGHT PER GALLON

9.6 lb.

AVERAGE NONVOLATILE

57% by weight

DRYING TIME

Touch: 4 hours

Through: 48 hours

The drying time depends on the temperature, humidity and film thickness.

SAFETY

Flammability:

Wet: Flash point 110° F (43° C)

Threshold Limit Value of Solvent Vapor (TLV): 100 ppm

LIMITATIONS

The solvent in this product may attack plastic foams. Test compatibility before using.

Do not apply to roof surfaces with less than 1" pitch per linear foot. Continuous immersion caused by constant ponding of water should be avoided.

Do not use this product in food storage areas where the solvent vapor can contaminate food.

Apply between 20° F (6.7 C) and 110° F (43 C).

CAUTION

Combustible mixture. Do not use or store near heat, sparks, or open flame. Keep container closed when not in use. Vapor harmful. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Do not take internally. In an emergency, call a physician. Keep out of reach of children.

Max Voc = 4.1 lbs/gal or 491 grams/liter

DESCRIPTION

55-10 Eco-Vapor Cote is a low odor fire resistive vapor barrier coating designed for use on indoor or outdoor low temperature equipment. It applies easily by brush and dries to a smooth flexible finish.

SPECIFICATION COMPLIANCE

MIL-C-19565C

NFPA 90A & 90B

U.S. Department of Agriculture chemically acceptable.

U.S.C.G. 164.012/108/0

METHOD OF APPLICATION

Brush, glove, trowel, spray.

MATERIAL PREPARATION

Do not thin. Stir well.

APPLICATION

This product is for industrial use only. It should be applied by trained and qualified craftspeople.

Be sure surfaces are clean and dry.

When coating indoor equipment and piping apply a tack coat of Eco-Vapor Cote at a coverage rate of 50 sq. ft./gal. (.8 Liter/M2).

Thoroughly embed the reinforcing membrane into the wet tack coat. Overlap all edges and seal. Apply a finish coat of Eco-Vapor Cote at a coverage rate of 50 sq. ft./gal. (.8 Liter/M2).

CLEANUP

Mineral spirits or Xylol

ASBESTOS FREE

Flame Spread	10
Smoke Developed	10
Rate per Coat	50 sq.ft/gal

07/2017R

WARRANTY TERMS: The physical and chemical properties of this product are representative of the typical average values derived in accordance with test methods deemed acceptable, and can vary when subjected to normal manufacturing methods. These values are supplied only as a technical service and are subject to change notice. To be sure information is current call Mon-Eco Industries, Inc.

Terms of Warranty: Warrantor, Mon-Eco Industries, Inc. warrants satisfactory results of this product only when recommendations herein established are followed. The recommendations for use are established upon tests and information deemed reliable. We recommend that adequate testing be made by the user to determine if the product is suitable for the intended purpose and use. Warrantor assumes no responsibility beyond replacement or refund of the purchase price of this product, since warrantor has no control over the methods and application of its product, methods and conditions of transportation, handling and storage of the product. **WARRANTOR EXPLICITLY DISCLAIMS ALL LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE.** No agent or representative of Mon-Eco Industries, Inc. has the authority to change or extend these conditions.

MON-ECO INDUSTRIES, INC.

5 JOANNA COURT • EAST BRUNSWICK, NJ 08816
(732) 257-7942 • 800-899-6326 • FAX (732) 257-6525

www.mon-ecoindustries.com



HEATING, AIR-CONDITIONING & REFRIGERATION DISTRIBUTORS INTERNATIONAL